Shuttle®

xpc BAREBONE SK21G

Shuttle XPC Barebone SK21G delivers value!

The Shuttle XPC Barebone SK21G is the new benchmark for high-performance, high-value computing. It delivers the full processing power of the AMD Sempron processor, as well as superb integrated features and upgradeability, this small form factor (SFF) computer offers unmatched style, functionality and performance. From web surfing to DVD playback and gaming to office productivity, the XPC SK21G delivers the perfect combination of size, power and style.

The Shuttle XPC Barebone SK21G is an ideal: Digital hub (music, photos and video); Desktop replacement; Home media center; Home office platform.

Feature Highlight

G chassis	• Light aluminum chassis • Heat-pipe cooling with 9,2 cm fan • Bays: 1x 5.25“, 2x 3.5“
Chipset	• VIA K8M800CE / VT8237R+ • Integr. VIA UniChrome Pro Graphics
CPU	• Socket 754 • Supports AMD Sempron processors
Slots	• 1 x AGP 8X • 1 x PCI (32-bit)
Memory	• Supports DDR-400/333
Drive connectors	• 2x Serial-ATA 150 Raid • 1x IDE ATA 133 • 1x floppy
other connectors	• 6-channel audio • Firewire, USB 2.0, VGA • Fast Ethernet LAN
Power supply	• 200 Watt, Mini-Netzteil
Application	• Business

Article number: SK21G
Order number: PC-SK21G
UPC (see bar code)

8 11686 00084 6

© 2005 Shuttle Computer Handels GmbH (Germany)
All information provided by Shuttle is subject to change without notice.

Date: 18. Oct. 2005

Shuttle Computer Handels GmbH, Fritz-Strassmann-Strasse 5, D-25337 Elmshorn, Germany
Tel. +49 (0)4121 476-860 Fax. +49 (0)4121 476-900 Email: sales@spacewalker.de

www.shuttle.com

We create!

Specification

Chassis	G-type chassis made of aluminum, silver color, light acrylic front panel storage bays: 1 x 5.25", 2 x 3.5" (1 internal) dimensions: 30 x 20 x 18.5 cm (LWH) weight: 2.6 kg net / 5,1 kg gross Slim-line and pre-installed cabling removes airflow impedance and makes installation a snap
Mainboard	Shuttle FX21, Shuttle form factor, proprietary design for SK21G Chipset: VIA K8M800CE + VIA VT8237R+ Phoenix/AwardBIOS, 4MBit flash memory with hardware monitoring and ACPI power management functions dimensions: 25.4 x 18.5 cm
Power supply	200 Watt mini PSU, supports 115/230V Active PFC: Power-Factor-Correction with active components connectors: 20-pin ATX, 4-pin ATX12V, Power cord: region specific EMI Certified: FCC, CE, BSMI – Safety Certified: UL, TÜV, CB
Processor support	Socket 754 supports AMD Sempron processors supports CPU models 2500+ ~ 3700+
Processor cooling	Shuttle I.C.E. (Integrated Cooling Engine) advanced Heatpipe technology, linear fan control, 92mm cooling fan
Memory support	2 x 184 pin slots supports PC3200/2700/2100 (DDR400/333/266) DDR SDRAM memory up to a total size of 2GB
Slots	1 x AGP 8X/4X 1 x 32 Bit PCI (v2.2)
Graphics	VIA UniChrome Pro 128-bit 2D/3D graphics engine DirectX 9.0 compliant, shared Memory max. 64MB
6-channel audio	5.1 channel AC97 audio controller Connectors: line-out (6-ch), line-in, microphone, 2x CD-in
LAN Controller	Fast Ethernet network controller supports 10 / 100 MBit/s opteration
Firewire Controller	IEEE1394 Firewire controller VIA 6307 with 2 Firewire connectors (1x front and 1x rear) supports 400Mb/s, 200Mb/s, 100Mb/s data transfer rate
Drive connectors	2 x Serial-ATA 150 , supports RAID 0, 1, JBOD 1 x IDE ATA 133 drives, 1 x floppy disk drive
Front Panel connectors	Microphone, Headphone (Line-out), Line-in 2x USB 2.0, Firewire (4 pol.)
Back Panel connectors	VGA connector for monitor, Firewire (6 pin), PS/2 for mouse and keyboard, LAN (RJ45) 4 x USB 2.0, Serial port (COM), Clear CMOS button 6-ch Audio line-out (2x rear/front, bass/center), Line-in optional Wireless LAN module, optional parallel port
Internal connectors	2 x USB 2.0 (total 8x), 2 x CDROM inputs, 2 x fan connectors, 1 x SPDIF (input/output)
Accessories	Shuttle I.C.E. Thermal Module (heat-pipe), floppy cable, ATA133 cable, Serial-ATA cable, Power cord, Driver CDROM, Multilanguage User Manual

© 2005 Shuttle Computer Handels GmbH (Germany)
All information provided by Shuttle is subject to change without notice.

Date: 18. Oct. 2005

Shuttle Computer Handels GmbH, Fritz-Strassmann-Strasse 5, D-25337 Elmshorn, Germany
Tel. +49 (0)4121 476-860 Fax. +49 (0)4121 476-900 Email: sales@spacewalker.de